

SPAN™

4.5" DUPLEX GAUGE SPECIFICATIONS

- **CASE MATERIAL** - Zytel nylon
- **BEZEL MATERIAL** - Stainless Steel
- **SOCKET** - Bronze equipped with Kem-X diaphragm protection
- **BOURDON TUBE** - 316 Stainless Steel filled with low temperature material
- **CONNECTION** - 1/4" Male NPT Lower back, side by side
- **LENS** - Acrylic
- **FILL FLUID** - Glycerin
- **DIAL** - White with black markings
- **ACCURACY** - $\pm 1\%$ of scale
- **POINTERS** - 1 Red, 1 Black
- **TEMPERATURE COMPENSATION** Internal breathing diaphragm
- **PRESSURE RANGES AVAILABLE** 0-300, 0-400, 0-600 PSI
- **MODEL NUMBERS** - DPX-410



▲ DPX-410 - 4.5" DUPLEX LIQUID FILLED GAUGE

▼ IPS-224 - 2.5" INDICATING PRESSURE SWITCH

SPAN™

2.5" INDICATING PRESSURE SWITCH

FEATURES

- 2.5" Polished brass case
- Compact size
- Precalibrated switch point
- Easy field adjustment
- Brass or Stainless Steel internals

SPECIFICATIONS

- **SWITCH DIFFERENTIALS** - $5\% \pm 1\%$ of range. (Switching differential may vary on Stainless Steel or high pressure units.)
- **SWITCH TYPE** - SPDT
- **TEMPERATURE** - -40° to 180°F
- **LOAD** - 15 Amps, 125 or 250V AC
- **LIFE EXPECTANCY** - 1,000,000 operations minimum
- **PRESSURE RANGES AVAILABLE** 200 to 5,000 PSI
- **MODEL NUMBERS**
IPS-220 IPS-224 IPS-222

